

GHXV.EX27076 Proportioners, Foam Concentrate

Page Bottom

Proportioners, Foam Concentrate

See General Information for Proportioners, Foam Concentrate

EUROTECH FIRE PROTECTION LTD

EX27076

The Business Centre Unit 6 Molly Millars Lane Wokingham, RG41 2QZ UNITED KINGDOM

BLADDER TANK AND RATIO-FLOW CONTROLLER INVESTIGATED TO UL 162

53 to 3963 gal capacity ASME for vertical and horizontal installation.

Following are equivalent length valves for the controllers (EUROSAFE) based on a roughness factor of 130 and schedule 40 steel pipes:

Model	Equivalent Length Ft
2	22.0
3	17.5
4	29.3
6	24.9
8	23.0

Refer to the individual foam concentrate Listings for operating limitations with specific combinations of foam concentrates and proportioners.

Last Updated on 2016-02-15

Page Top **Questions?** Print this page Terms of Use

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a nonmisleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".